(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 8 July 2004 (08.07.2004)

PCT

(10) International Publication Number WO 2004/056629 A1

- (51) International Patent Classification7: B60T 7/08, 11/00
- (21) International Application Number:

PCT/NO2003/000439

(22) International Filing Date:

23 December 2003 (23.12.2003)

(25) Filing Language:

Norwegian

(26) Publication Language:

English

(30) Priority Data: 20026230

23 December 2002 (23.12.2002) NO

- (71) Applicants and
- (72) Inventors: VIK, Per, Espen [NO/NO]; Naustheller, N-5394 Kolbeinsvik (NO). VIK, Lars, Eivind [NO/NO]; Nordre Vik, N-5394 Vinnevåg (NO).
- (74) Agent: A/S BERGEN PATENTKONTOR; P.O. Box 1998, Nordnes, N-5817 Bergen (NO).


- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

[Continued on next page]

(54) Title: DEVICE OF A BRAKE SYSTEM



(57) Abstract: A device is described for a parking brake system for vehicles, said parking brake comprises a brake lever that can reset the brake system between an active brake position and a neutral position, and also a transmission mechanism (18) to make it possible to reset the brake lever from the braking position, with the mentioned operation of the transmission mechanism (18) being dependent on the ignition system of the vehicle being activated/turned on. The device is characterised in that a blocking appliance with a blocking peg that is in blocking engagement with the transmission mechanism (18) when the appliance is not supplied with a voltage from the ignition system, and disengages from the blocking engagement with the mechanism (18) when the appliance is supplied with a voltage.